

CAI – ALON

Alumina for Mineral Fibres

The addition of alumina into the manufacture of mineral fibres (mineral wool, rock wool, stone wool) is a direct result of concerns over the bio-solubility of mineral fibres, their ability to be dissolved into the human blood system. Basically it was found that the higher the alumina content of mineral fibres, the more easily they were able to dissolve in blood, i.e. they have a low biopersistence. [1]

The typical chemical composition of mineral fibres with low biopersistence ranges 38-46% SiO₂, 15-38% CaO, 10-32% Al₂O₃, 2-10% MgO, 0.5-3% TiO₂, 0.3-7% FeO, 0.3-3% Na₂O, 0.3-1.3% K₂O. [2]

The aim of mineral wool manufacturers is to use in the raw material mix as high alumina content basalt and anorthosite as possible. If there is a need for additional alumina in the mixture, the obvious choice for an alumina source is bauxite.

A cost-effective substitute for bauxite is CAI-ALON, providing about 83 % Al₂O₃, on a calcined basis. The mineral components are corundum (alpha-Al₂O₃), spinel (MgO·Al₂O₃), aluminium nitride (AlN), metallic aluminium (Al), quartz (SiO₂) and small quantities of fluorides and chlorides (CaF₂, NaCl). CAI-ALON is a dry powder with a particle size of 95 % less than 0.3 mm.

CAI-ALON is produced by processing slag (dross) from melting aluminium metal. The advantageous use of processed aluminium slag materials in the production of mineral fibres is already state of technology since about 20 years [3-4]:

- faster smelting (due to the fine particle size),
- less energy for smelting (Al and AlN are exothermically converted to Al₂O₃),
- reduced smelting temperature, viscosity and surface tension (due to CaF₂ and NaCl).

In the production of mineral wool the feed for the shaft furnace typically used are lumps in the size of about 10-20 cm or briquettes of recycled fibre material, mixed with fine grained materials (fly ash, blast furnace slag, and cement as binder). Processed aluminium slag powder can be added to the mixture of the briquettes or even directly injected into the melt. [5-6]

Literature

[1] M. O'Driscoll: Alumina in a spin. *Industrial Minerals*, August 2006, 36-43

[2] T. Knudsen, M. Guldberg, V.R. Christensen, S.L.Jensen: New type of stonewool (HT fibres) with a high dissolution rate at pH =5. *Glastech. Ber. Glass Sci. Technol.* 69 (1996) No. 10, 331-337.

[3] WO 91/0150: Process for producing mineral fibers incorporating an alumina-containing residue from metal melting operation and fibers so produced. ALCAN INTERNATIONAL LIMITED, Canada. Priority data: 31 July 1989.

[4] WO 99/28253: Production of man-made vitreous fibres. ROCKWOOL INTERNATIONAL A/S, Denmark. Priority data: 2 December 1997

[5] WO 99/28252: Briquettes for mineral fibre production and their use. ROCKWOOL INTERNATIONAL A/S, Denmark. Priority data: 2 December 1997

[6] WO 99/28249: Apparatus and method for the production of man-made vitreous fibres. ROCKWOOL INTERNATIONAL A/S, Denmark. Priority data: 2 December 1997

Reinhard Feige

Consultant, Expert

Industrial Minerals and Ceramic Materials

* Alumina and Alumina Waste Materials

* Refractory Ceramics for Aluminium and Zinc

Sternenburgstr. 64a, D- 58332 Schwelm / Germany

Tel.: +49-2336-8190603; Mobile: +49-171-8313133;

feige@alumina.de; www.alumina.de

2015-03-17